nday	No.		

CERTIFICATE OF LOCATION	OF GOVERNMENT CORNER		
EAST QUARTER Corner of Section 14	, Township <u>102 N</u> , Range <u>43 W</u> , 5th P.M.		
STATE OF MINNESOTA, County of NOBLES			
At the corner location shown on the sketch:			
☑ On 11/12/02 found a 5/8" REROD			
DATE			
☑ left monument as found, ☐ lo ☐ Onplaced a	wered monument,   removed monument (explain)		
SKETCH OF R	EFERENCE TIES		
	<b>†</b>		
ካ - <b>N</b> -	NORTHEAST CORNER		
Ţ	SECTION 14—102—43 CALCULATED POSITION		
NE 1/4 SEC 14-102-43			
	NW 1/4 SEC 13-102-43		
EAST 1/4 CODNED			
EAST 1/4 CORNER SECTION 14-102-43	1		
5/8" REROD			
<b>ົ</b> ຫ			
SE 1/4 SEC 14-102-43	014 4 4 4 6 7 0 40 40 40		
<u> </u>	SW 1/4 SEC 13-102-43		
MADRY (1006 AD HISTAFAIT)	SOUTHEAST CORNER		
NADB3 (1996 ADJUSTMENT)  STATE PLANE COORDINATES	SECTION 14-102-43 5/8" REROD		
NOBLES COUNTY DATUM	JO KENOD		
N= 150211.222 E= 499177.464	BOOK: NOBLES CO. PG. 23 I:\NOBLS\CERTIFICATES\E14-102-43		
Statement of evidence relative to this corne	er location is on back of page.		
hereby certify that this document and the	OFFICE OF THE COUNTY RECORDER		
data contained herein was prepared by me or under my direct supervision.	County of		
JANELE FOWLDS DATE	I hereby certify that this document was filed in the Co. Recorders office atM. on the		
Registration No. 26748	day of A.D., 19   County Recorder		
□ Land surveyor, □ Professional Engineer	By, Deputy		
•	DOCUMENT NO		
The control of the co	DOCUMENT NO.		

## Statement of Evidence

East Quarter Corner Section 14, Township 102 North, Range 43 West

According to the Original Survey notes located in the Secretary of States Office, the East Quarter of Section 14 was established as follows: North between Sections 13 & 14, Variance 10 degrees 45 minutes, at 40.00 chains set a post in mound with pits for the Quarter Section Corner.

1891	Nobles County Highway Department records show an iron pin.
1897	Nobles County Highway Department records show an iron pin.
1902	Nobles County Highway Department records show an iron pin.
2002	On November 12, Bolton & Menk, Inc. found a 5/8" Rerod 1' below the surface.