Index	No.	
IIIIUEX	110.	 

CERTIFICATE O	F LOCATION	I OF	GOVER	NMENT	CORNER
EAST QUARTER	Corner of Section 9	, Towr	nship <u>102 N</u> ,	Range 43 W	_, 5th P.M.
STATE OF MINNESOTA, Cou	nty of NOBLES	•••			
At the corner location sho	wn on the sketch:				
☑ On 11/13/02 fou	nd a <u>5/8" REROD</u>				·
	ument as found, 🗆 i ed a	owered m	onument, 🗆 r	emoved monul	ment (explain)
	SKETCH OF	REFEREN	CE TIES		
EAST	1/4 CORNER CTION 9-102-43 5/8" REROD		NW 1/4	SEC 10-10	02-43
SE 1/4 SE  NAD83 (1996 ADJUSTMENT) STATE PLANE COORDINATES NOBLES COUNTY DATUM	TA 0 100 / 2	2664.50	SW 1/4 SOUTHEAST - SECTION 9-10 BRASS PLUG		2-43
N= 155585,426			•		
E= 488614.454					K: NOBLES CO. PG. 27 RTIFICATES\E9-102-43
Statement of evidence r	elative to this corn	er locat	ion is on ba	· · · · · · · · · · · · · · · · · · ·	
I hereby certify that this data contained herein was under my direct supervision Janele Fowlds  Registration No2674	prepared by me of on.  [0]4/05 DATE	County I hereb in the	Co. Recorder	t this docun	nent was filed M. on the A.D., 19
■ Land surveyor, □P		_			, Deputy
□ County Surveyor. □ County Engineer			ENT NO		

## Statement of Evidence

## East Quarter Corner Section 9, Township 102 North, Range 43 West

According to the Original Survey notes located in the Secretary of States Office, the East Quarter of Section 9 was established as follows: North between Sections 9 & 10, Variance 11 degrees 15 minutes, at 40.00 chains set a post in mound with pits for the Quarter Section Corner.

1892	Nobles County Highway Department records show a stone was set.
1938	Nobles County Highway Department records show an iron pin.
2002	On November 13, Bolton & Menk, Inc. found a 5/8" Rerod 0.4' below the surface in township road.