CERTIFICATE OF LOCATION	OF GOVERNMENT CORNER
NORTH QUARTER Corner of Section 14	_, Township <u>102 N</u> , Range <u>43 W</u> , 5th P.M.
STATE OF MINNESOTA, County of NOBLES	
At the corner location shown on the sketch:	
☑ On 11/08/02 found a NOTHING	
DATE	
	vered monument, removed monument (explain) OSITION HALF WAY AND ON LINE BETWEEN T. CORNERS
THE NORTHEAST AND THE NORTHWES	CORNERS
SKETCH OF R	EFERENCE TIES
- N -	
SW 1/4 SEC 11-102-43	
·	SE 1/4 SEC 11-102-43
NORTH 1/4 CORNER SECTION 14-102-43 CALCULATED POSITION	
2652.80	2652.80'
NORTHWEST CORNER SECTION 14-102-43	NORTHEAST CORNER SECTION 14-102-43 CALCULATED POSITION
CAPPED IRON PIPE	CALCUBATED POSITION
NW 1/4 SEC 14-102-43	NE 1/4 SEC 14-102-43
NAD83 (1996 ADJUSTMENT) STATE PLANE COORDINATES NOBLES COUNTY DATUM	
N= 152922.522 E= 496556.322	BOOK: NOBLES CO. PG. 2
Statement of evidence relative to this corne	er location is on back of page.
I hereby certify that this document and the data contained herein was prepared by me or	OFFICE OF THE COUNTY RECORDER
under my direct supervision.	County of
	I hereby certify that this document was filed in the Co. Recorders office atM. on the
JANELE FOWLDS DATE	day of A.D., 19
	unj uni
Registration No. <u>26748</u>	County Recorder
Registration No. <u>26748</u> ☑ Land surveyor, ☐ Professional Engineer	County Recorder

Statement of Evidence

North Quarter Corner Section 14, Township 102 North, Range 43 West

According to the Original Survey notes located in the Secretary of States Office, the North Quarter of Section 14 was established as follows: East on a random line between Sections 11 & 14, Variance 11 degrees, at 40.00 chains point for quarter corner is in the river, at 80.06 chains intersect North South line 20 links South of the corner to Sections 11, 12, 13, & 14. South 89 degrees 52 minutes West, between Sections 11 & 14, Variance 11 degrees, at 40.03 chains point for quarter corner in river. Set post in mound with pits for witness corner, 4.00 chains West of true corner.

2002

On November 8, Bolton & Menk, Inc. searched for the corner and found nothing. Bolton & Menk, Inc. calculated a position half way and on line between the Northeast and the Northwest Section Corners.