

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

NORTH QUARTER Corner of Section 20, Township 102 N, Range 43 W, 5th P.M.

STATE OF MINNESOTA, County of NOBLES


At the corner location shown on the sketch:

☒ On 11/12/02 found a 5/8" REROD
DATE

☒ left monument as found, ☐ lowered monument, ☐ removed monument (explain)

☐ On _____ placed a _____
DATE

SKETCH OF REFERENCE TIES



SW 1/4 SEC 17-102-43

SE 1/4 SEC 17-102-43

NORTH 1/4 CORNER
SECTION 20-102-43
5/8" REROD

NW 1/4 SEC 20-102-43

NE 1/4 SEC 20-102-43

NAD83 (1996 ADJUSTMENT)
STATE PLANE COORDINATES
NOBLES COUNTY DATUM

N= 147732.546

E= 480571.122

BOOK: NOBLES CO. PG. 13

I:\NOBLES\CERTIFICATES\N20-102-44

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

Janele Fowlds
JANELE FOWLDS

10/4/05
DATE

Registration No. 26748

☒ Land surveyor, ☐ Professional Engineer

☐ County Surveyor, ☐ County Engineer

OFFICE OF THE COUNTY RECORDER

County of _____

I hereby certify that this document was filed in the Co. Recorders office at _____ M. on the _____ day of _____ A.D., 19____

County Recorder _____

By _____, Deputy

DOCUMENT NO. _____

Statement of Evidence

North Quarter Corner Section 20, Township 102 North, Range 43 West

According to the Original Survey notes located in the Secretary of States Office, the North Quarter of Section 20 was established as follows: East on a random line between Sections 17 & 20, Variance 11 degrees 45 minutes, at 40.00 chains set temporary quarter post, at 79.82 chains intersect North South line 12 links South of the corner to Sections 16, 17, 20, & 21. South 89 degrees 55 minutes West, between Sections 17 & 20, Variance 11 degrees 45 minutes, at 39.91 chains set post in mound with pits for the Quarter Section Corner.

2002 On November 12, Bolton & Menk, Inc. found a Nail in gravel road, removed nail and found a 5/8" Rerod 0.5' below the surface.