Indev	NI.		
INNAY	NO.		

.1. 21. .

**

CERTIFICATE OF LOCATION	OF GOVERNMENT CORNER
NORTHEAST Corner of Section 23 STATE OF MINNESOTA, County of NOBLES At the corner location shown on the sketch: On 11/12/02 found a 5/8" REROD DATE	, Township <u>102 N</u> , Range <u>43 W</u> , 5th P.M.
□ On placed a DATE	wered monument, 🗆 removed monument (explain)
SKETCH OF R	EFERENCE TIES
-N- SE 1/4 SEC 14-102-43	EAST 1/4 CORNER SECTION 14-102-43 5/8" REROD
NE CORNER SECTION 23-102-43 5/8" REROD	SW 1/4 SEC 13-102-43
NORTH 1/4 CORNER SECTION 23-102-43 STONE MONUMENT	2649.91' NORTH 1/4 CORNER SECTION 24-102-43 3/4" IRON PIPE
NE 1/4 SEC 23-102-43	NW 1/4 SEC 24-102-43
NAD83 (1996 ADJUSTMENT) STATE PLANE COORDINATES NOBLES COUNTY DATUM	
N= 147619.126 E= 499155.954	BOOK: NOBLES CO. PG. 22 I:\NOBLS\CERTIFICATES\NE23-102-43
Statement of evidence relative to this corne	
I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.	OFFICE OF THE COUNTY RECORDER County of
JANELE FOWLDS DATE	I hereby certify that this document was filed in the Co. Recorders office atM. on the A.D., 19
Registration No. <u>26748</u>	County Recorder
□ Land surveyor, □ Professional Engineer □ Country Training	By, Deputy
│ □ County Surveyor, □ County Engineer │	DOCUMENT NO.

- 13 - 13 - 4

Statement of Evidence

Northeast Corner Section 23, Township 102 North, Range 43 West

According to the Original Survey notes located in the Secretary of States Office, the Northeast Corner of Section 23 was established as follows: North between Sections 23 & 24, Variance 11 degrees, at 80.00 chains set a post in mound with pits for the corner to Sections 13, 14, 23, & 24.

1891	Nobles County Highway Department records show a stone monument.
1902	Nobles County Highway Department records show a stone monument.
2000	On November 2, Zieske Land Surveying, Inc. found a ¾" iron stake, 2649.90 feet from the North Quarter of Section 24-102-43.
2002	On December 12, Bolton & Menk, Inc. found a 5/8" Rerod at the intersection on two township roads 0.2' below the surface.
	The evidence is not conclusive as to the true corner location, however the occupational and collateral evidence suggest that this is a reasonable location as to

The evidence is not conclusive as to the true corner location, however the occupational and collateral evidence suggest that this is a reasonable location as to the corner. Additional information regarding the preparation of this certificate can be obtained by contacting: Bolton & Menk, Inc., Mankato, MN.