CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

NORTHWEST Corner of Section 18, Township 102N, Range 43W, 5th P.M.

STATE OF MINNESOTA, County of NOBLES


At the corner location shown on the sketch:

☒ On 2/28/2006 (DATE) found a PK NAIL IN C/L OF E-W ROAD, 2± WEST FROM NORTH ROAD C/L & 4± EAST FROM SOUTH ROAD C/L.

☒ left monument as found, ☐ lowered monument, ☐ removed monument (explain)

☐ On _____ (DATE) placed a _____

SKETCH OF REFERENCE TIES



● MONUMENT INPLACE

○ MONUMENT SET

NOT TO SCALE

NO OTHER TIES AVAILABLE

BEARING SYSTEM IS BASED ON MN, STATE PLANE COORDINATE SYSTEMS, SOUTH ZONE.

N: 570,135.25
E: 2,081,166.26
MN SOUTH ZONE
NAD 1983
NOT TO SCALE

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

Thomas V. Zeff — 6/29/06 (DATE)

Thomas V Zeff

Registration No. 44563

☒ Land Surveyor, ☐ Professional Engineer

☐ County Surveyor, ☐ County Engineer

OFFICE OF THE COUNTY RECORDER

County of _____

I hereby certify that this document was filed in the Co. Recorders office at ____ .M. on the ____ day of _____ A.D., 20____

County Recorder _____

By _____, Deputy

DOCUMENT NO. _____

STATEMENT OF EVIDENCE:

NORTHWEST CORNER, SECTION 18, T. 102 N., R. 43 W.,
NOBLES COUNTY, MINNESOTA

1867 Thomas B. Walker, US. Deputy Surveyor, monumented corner.

2/28/2006 Ulteig Engineers, Inc., Survey Crew, Dennis Lavallie Party Chief found a PK nail in the C/L of the E–W asphalt pavement, approx. 2' west from the north road C/L and approx. 4' east from the south road C/L.
Ties: E–2662.22' to North 1/4 corner, Section 18;
S–2628.56' to West 1/4 corner, Section 18;
W–2645.55' to North 1/4 corner, Section 13, Range 44.