	A CARCOLOGIC		
Index	No		

				Index No
CERTIFICATE O	F LOCATION	OF G	OVERNMEI	NT CORNER
NORTH QUARTER	Corner of Section 34	_, Township		40 , 5th P.M.
STATE OF MINNESOTA, Cou	nty of NOBLES			
At the corner location sho				
☑ On 4/2006 fou	nd a SPIKE HALF WA	Y AND ON	LINE BETWEEN	THE SOUTHEAST
DATE	SECTION CORNERS			**
	ument as found, 🗆 Iow	rered monur	ment, 🛛 removed	monument (explain)
	ced a <u>3/4" CAPPED</u>	IRON PIPE	IN PLACE OF S	PIKE
DATE			5	
	SKETCH OF RE	FERENCE	TIFS	
1	SKETOTI OT THE		25	
4	2.*			
- Ņ -				
SW	* .*.*		SE 1/4	
SEC 27-	3000	× 	SEC 27-10	
		FENCE	2' EAST	
			3	NE CORNER
NW CORNER		NAIL & FENCE	DOST FUUND	SECTION 34-104-4() 1/2" IRON SHAFT 16
SECTION 34-104-40 FOUND REBAR 4" DEEP	ě	32.9'	DEEP	SET CAPPED IRON PIPE #43909 ON TOP
2622	.90		2622.90	
NAI	L & DISK IN	N 1/4	CORNER	
	ENCE POST 32.4'		34-104-40 PIKE, SET CAPPED	
NW 174 SEC 34-104-40	FENCE 9' WEST			
320 34-104-40	× 1			
NAD83 (1996 ADJUSTMENT)	7	Х	NE 1/2	<i>i</i> ,
STATE PLANE COORDINATES NOBLES COUNTY DATUM		ľ	SEC 34-10	14-40
N= 200814.725				
E= 586300.572				NOBL CO. BK 1, PG. 53-5
				CERTS\CAD\NQC27-104-40.DW
Statement of evidence	relative to this corne	er location	is on back of	page.
I hereby certify that this data contained herein w	g document and the	OFFICE O	F THE COUNTY	RECORDER
data contained herein wo under my direct supervis	County of			
//////////////////////////////////////		I hereby	certify that this	document was file ce atM. on th
JOSEPH A. HAEFNER	DATE			A.D., 20_
Registration No. 439		I .	160	
□ Land surveyor, □		(I)		, Deput
☐ County Surveyor, ☐		1		, , , , ,
			000 / 0000 / T	
	2			