	DIV
Index _	P-13

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER		
EAST QUARTER Corner of Section	on <u>21</u> , Township <u>104N</u> , Range <u>41W</u>	
5th Principal Meridian, State of Minnesota, County of Nobles.		
At the corner location shown on the sketch:		
On		
	d monument	
	SURF IS SOLD	
On placed a		
SKETCH OF REFERENCE TIES		
SET PK IN PP	S89*E -O 25.11' -O SET 3/8" REBAR -N-	
Statement of evidence for this corner location is on back of this page.		
I hereby certify that this document was researched and prepared by me or under my direct supervision and that I am a licensed Land Surveyor under the laws of the State of Minnesota.	DOCUMENT NUMBER A 357581 Certified, Filed and or Recorded or March 07, 2018 3:50 PM	
Signature FML:	Lyon Wilson	
Signature	NOBLES COUNTY RECORDER LYNN M. WILSON 507-295-5268	
Title:	Pagas: Z	
X Land Surveyor Professional Engineer		
☐ County Surveyor ☐ County Engineer		

KRIS WROOLIE Minnesota License No. 49563

Statement of Evidence:

P-13

East Quarter Corner of Section 21, Township 104 North, Range 41 West, 5th Principal Meridian, Nobles County, Minnesota.

1868-Deputy Surveyor set a post in mound with pits.

1993 - Nobles County Highway Department "Corner Ties Book" notes an excavation was performed and nothing was found. A 3/4" by 24" outside diameter iron pipe was set at obliterated position on centerline of township road and fence line west by Madsen Surveying. The following tie was made:

Bottle cap in fence post

West

74.45

2017 - Westwood field crews recover an iron pipe with LS 13593 cap down 0.4' on centerline north/south and fence line west. Ties were set or found as shown on the front of this certificate.

Analysis of the recovered data, field evidence and survey measurements, indicates that the monument found is the correct perpetuation of this corner. For additional information concerning this corner please contact Westwood Professional Services.

1/29/18