



Index \_\_\_\_A-5

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER	
NORTHEAST Corner of Section	n <u>6</u> , Township <u>103N</u> , Range <u>42W</u>
5th Principal Meridian, State of Minnesota, County o	f Nobles.
At the corner location shown on the sketch:	
X On 12/6/17 found a PK NAIL 9.4' SOUTH OF THE CENTERLINE INTERSECTION	
☐ left monument as found ☐ lowered monument ☐ removed monument (explain)	
Onplaced a	
SKETCH OF REFERENCE TIES	
CENTER OF RURAL WATER SERVICE GATE VALVE	FOUND NAIL AND BOTTLE CAP  IN TOP OF CORNER POST  (1997)  X  AD (5)
CSAH 16	
501°W	FOUND NAIL AND BOTTLE CAP W. FACE OF CORNER POST (1997)  N.T.S.
Statement of evidence for this corner location is on back of this page.	
I hereby certify that this document was researched and prepared by me or under my direct supervision and that I am a licensed Land Surveyor under the laws of the State of Minnesota.	DUCUMENT NUMBER A 357391 Certified, Filed and or Recorded on February 28, 2018 12:40 PM
Signature + 1/8/18 License No. 49563	Lynn Wilson
Date 1/8/18 License No. 49563 Title:	NOBLES COUNTY RECORDER LYNN M. WILSON 507-295-5268
X Land Surveyor ☐ Professional Engineer	Pages: 2
County Surveyor County Engineer	

## KRIS WROOLIE Minnesota License No. 49563

## **Statement of Evidence:**

A-5

Northeast Corner of Section 6, Township 103 North, Range 42 West, 5<sup>th</sup> Principal Meridian, Nobles County, Minnesota.

- 1869-Deputy Surveyor set a post in mound with pits.
- 1902- Nobles County Highway Department "Corner Ties Book" calls for a stone to mark the corner location.
- 1917- Nobles County Highway Department "Corner Ties Book" calls for a stone to mark the corner location.
- 1922- Nobles County Highway Department "Corner Ties Book" calls for a stone to mark the corner location.
- 1943- Nobles County Highway Department "Corner Ties Book" calls for a placed 2x2 hub to mark the corner location.
- 1955- Nobles County Highway Department "Corner Ties Book" calls for a stake to mark the corner location.
- 1967- Nobles County Highway Department "Corner Ties Book" calls for a stone and placed wood stake to mark the corner location and set ties
- 1979- Nobles County Highway Department "Corner Ties Book" calls for an iron rod to mark the corner location.
- 1997- Madsen Land Surveying set a 3/4" pin
- 2016- Nobles County Highway Department "Corner Ties Book" calls for a PK nail was set after an overlay to mark the corner location.
- 2017- Westwood Professional Services recovered a PK nail with a magnetic indication under it at the centerline intersection and ties from 1997. Position agrees with highway plan. Accepting as the best available evidence for the corner. Ties were found or set as shown on the front of this certificate.

Analysis of the recovered data, field evidence and survey measurements, indicates that the monument found is the correct perpetuation of this corner. For additional information concerning this corner please contact Westwood Professional Services.