Index \_\_\_\_T-5

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER	
EAST QUARTER Corner of Section	on <u>30</u> , Township <u>104N</u> , Range <u>42W</u>
5th Principal Meridian, State of Minnesota, County of Nobles.	
At the corner location shown on the sketch:	
X         On         12/27/2017         found         NO EVIDENCE.	
☐ left monument as found ☐ lowered monument ☐ removed monument (explain)	
X On <u>12/27/2017</u> placed a 1 <u>/2" REBAR CAPP</u>	ED LS 49563 DOWN 0.4' ON CENTERLINE.
SKETCH OF REFERENCE TIES	
DILLMAN AVE	SET MAG IN S. FACE  OF CORNER POST  **
SET 3/8" REBAR WITH O	SET 3/8" REBAR WITH REFERENCE CAP  N.T.S.
Statement of evidence for this corner location is on back of this page.	
I hereby certify that this document was researched and prepared by me or under my direct supervision and that I am a licensed Land Surveyor under the laws of the State of Minnesota.	DOCUMENT NUMBER A 357529 Certified, Filed and or Recorded o March 07, 2018 9: 20 AM
Signature	NOBLES COUNTY RECORDER LYNN M. WILSON 507-295-5268
X Land Surveyor Professional Engineer	t Pages: 2
☐ County Surveyor ☐ County Engineer	С

## KRIS WROOLIE Minnesota License No. 49563

## **Statement of Evidence:**

T-5

East Quarter Corner of Section 30, Township 104 North, Range 42 West, 5<sup>th</sup> Principal Meridian, Nobles County, Minnesota.

1868-T.B. Walker set a post in mound with pits for the section corner.

2017- Westwood Professional Services did not locate any evidence of the corner. A 5/8" rebar capped 49563 was placed midway between section corners and on centerline. This position agrees with field lines to the east and west. Tie were set as shown on the front of this certificate.

Analysis of the recovered data, field evidence and survey measurements, indicates that the monument found is the correct perpetuation of this corner. For additional information concerning this corner please contact Westwood Professional Services.

2/1/5