CERTIFICATE OF LOCATION OF	GOVERNMENT CORNER
NORTHEAST Corner of Section 3 , Tov	wnship <u>104N</u> , Range <u>42W</u> , <u>5th</u> P.M.
STATE OF MINNESOTA, County ofNOBL	ES
At the corner location shown on the sketch:	
□ On found a	
□ left monument as found, □ lowered monument, □ removed monument (explain) ☑ On <u>03/07/2006</u> placed a <u>5/8" REBAR WITH CAP: RLS 44563 IN GRAVEL ROA</u> D. DATE	
N SKETCH OF REFERENCE TIES	
W ulteig E COUNTY HWY 71	1st ST
	SET 5/8" REBAR W/CAP: RLS 44563 T105N
_ s	T104N
GRAVEL ROAD	GRAVEL ROAD
TELEPHONE PEDESTAL MEASURED FROM TOP CENTER OF TP BOX ITP	STOP SIGN
WOOD FENCE POST W/NAIL 'X' ON SIDE FIELD ERICKSON A MIN. MAINTEN DIRT ROA	ANCE .
N: 642,930.77 E:2,136,060.42 MN SOUTH ZONE, NAD 83	
NOT TO SCALE BEARING SYSTEM IS BASED ON MN STATE PLANE COORDINATES, SOUTH ZONE. D53	
Statement of evidence relative to this corner location is on back of page.	
I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.	OFFICE OF THE COUNTY RECORDER County of I hereby certify that this document was filed in
Thomas V. Zeal DATE	the Co. Recorders office atM. on the A.D., 20
Registration No. 44563	County Recorder
☑ Land Surveyor, ☐ Professional Engineer	By, Deputy
☐ County Surveyor, ☐ County Engineer	DOCUMENT NO

STATEMENT OF EVIDENCE:

NORTHEAST CORNER, SECTION 3, T.104N., R.42W., NOBLES COUNTY, MINNESOTA

1858

W.J. NEALY, U.S. DEPUTY SURVEYOR, NORTH TOWNSHIP LINE.

03/07/2006

ULTEIG ENGINEERS, INC., SURVEY CREW, BRIAN PAYNE, PARTY CHIEF, FOUND NOTHING, SET 5/8" REBAR WITH CAP: RLS 44563, SO AS TO HARMONIZE SINGLE PROPORTIONAL DISTANCES ALONG THE TOWNSHIP LINE AS SHOWN ON PLSS TOWNSHIP PLAT FOR T104N, R42W, 5th PRINCIPAL MERIDIAN.

TIES: SW-58.4 TO TELEPHONE PEDESTAL, TOP CENTER OF PED BOX SW-58.0' TO WOOD FENCE POST W/NAILS "X" ON SIDE SE-48.0' TO STOP SIGN POST.